



*Estimated

N/A-Not Applicable

N/R-Not Restricted
N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

IDENTITY (As shown on Label or package) PC663#40 Pink Pigment Blend			PART NO. IF APPLICABLE		
SECTION I					
MANUFACTURER'S NAME Plasti Dip International, Inc.			EMERGENCY PHONE No. USA only: 1-800-424-9300 INT'L: 703-527-3887		
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3920 Pheasant Ridge Drive Blaine, MN 55449			REVISION #		
			MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156		
			DATE MSDS WAS PREPARED November 26, 2012		
SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.					
HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)	% Wt. (OPTIONAL)	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMEND
Propylene Glycol Monomethyl Ether Acetate	15 - 25	108-65-6	N/A	N/A	none
Xylene	1 - 5	1330-20-7	100 ppm	100 ppm	none
Ethylbenzene	0.1 - 1.0	100-41-4	100 ppm	100 ppm	none
Carbon Black	<1	1333-86-4	3mg/m ³	3mg/m ³	none
SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS					
BOILING POINT 282°F	SPECIFIC GRAVITY N/E		APPROXIMATE WEIGHT PER GALLON (LBS) N/E		
VAPOR PRESSURE 6 mmHg @ 20°C	VAPOR DENSITY (AIR = 1) Heavier than Air		EVAPORATION RATE (BUTYL ACETATE =1) N/A		
	% VOLATILE 16 - 25% VOC LBS/GAL 2.5 - 4.0		OTHER (IF ANY) None		
APPEARANCE AND ODOR White Liquid					
SECTION IV - FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (METHOD USED) 110.0°F		FLAMMABLE LIMITS	LEL 1.0	UEL 13.0	
EXTINGUISHING MEDIA water spray, dry chemical, carbon dioxide, foam					
SPECIAL FIRE FIGHTING PROCEDURES Wear self contained breathing apparatus and protective gear.					
UNUSUAL FIRE. EXPLOSION HAZARDS None Known.					
HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide. Metal oxide fumes.					
EXPLOSIVE LIMITS (% BY VOLUME IN AIR) 1.0 - 13.0					
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION					
HAZARD RATING 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV		National Fire Protection Association (NFPA) FIRE <u>2</u> REACTIVITY <u>1</u> HEALTH <u>2</u> SPECIAL HAZARDS <u>0</u>			

--	--

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AND STABILITY DATA			
STABILITY	UNSTABLE STABLE X	CONDITIONS TO AVOID None	
INCOMPATIBILITY (Materials to Avoid) Strong Oxidizers			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Dioxide and/or Carbon Monoxide. Metal oxide fumes.			
HAZARDOUS POLYMERIZATION	MAY OCCUR WILL NOT OCCUR X	CONDITIONS TO AVOID Sensitivity to static discharge is expected.	
SECTION VII - HEALTH HAZARD DATA			
ROUTES OF ENTRY	INHALATION? yes	SKIN? yes	INGESTION? yes
HEALTH HAZARDS	ACUTE X CHRONIC X		
CARCINOGENICITY: IARC 2B			
SIGNS AND SYMPTOMS OF EXPOSURE			
Inhalation: Headache, nausea, and irritation of nose, throat and lungs. Skin: Irritating upon repeated or prolonged contact. Eyes: Slightly irritating to eyes.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None Known			
EMERGENCY AND FIRST AID PROCEDURES			
Inhalation: Remove to fresh air. Skin: Wash areas with soap and water. Eyes: Flush thoroughly with water. See a physician if irritation persists. Ingestion: If swallowed, give large quantities of water. See a Physician immediately or contact poison control center.			
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED			
Dike and contain spill with inert material (sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep run-offs out of municipal sewers and open bodies of water.			
WASTE DISPOSAL METHOD Dispose of in accordance with local, state, federal regulations.			
PRECAUTIONS TO BE TAKEN IN HANDLING			
Avoid contact with eyes. Store in closed containers away from all possible sources of combustion. Use with adequate ventilation			

AND STORAGE

OTHER None

PRECAUTIONS**SECTION IX - CONTROL MEASURES**

RESPIRATORY PROTECTION (SPECIFY TYPE) None required		PROTECTIVE GLOVES Rubber gloves
VENTILATION	LOCAL EXHAUST Supplemental (if needed)	SPECIAL None
	MECHANICAL (GENERAL) To maintain exposure below PEL's	OTHER None
EYE PROTECTION Chemical splash goggles, or approved eye protection.		OTHER PROTECTIVE CLOTHING OR EQUIPMENT Chemical Apron/Eye bath/Safety Shower
WORK HYGIENIC PRACTICES Wash thoroughly after handling.		

SECTION X - TRANSPORTATION INFORMATION (Optional)

DOT PROPER SHIPPING NAME Paint Related Material	DOT HAZARD CLASS 3
DOT UN NUMBER UN 1263	DOT PACKING GROUP III

DOT EXCEPTIONS

A Flammable Liquid with a Flash Point at or above 100°F can be reclassified as a Combustible Liquid according to DOT 49CFR 173.120(b)(2).
 A Combustible Liquid is not regulated for ground transportation in the USA in non-bulk packaging (≤450 Liters or 119 Gallons) as long as it is not hazardous substance, a hazardous waste, or a marine pollutant according to DOT 49CFR 173.150(f)(2).

SECTION XI - 313 SUPPLIER NOTIFICATION

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).
 Xylene, and Ethylbenzene

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow

THE INFORMATION PROVIDED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM ITS USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND THE VENDORS CONTROL AND SINCE SUBSEQUENT DATA MAY SUGGEST MODIFICATION OF THE INFORMATION, VENDOR ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF ITS USE.