

# **SAFETY DATA SHEET**

Creation Date 13-Oct-2009 Revision Date 23-Jan-2018 Revision Number 5

1. Identification

Product Name Ethyl acetate

Cat No.: AC423680000; AC423680010; AC423680025; AC423680040;

AC423680250; AC423685000

**CAS-No** 141-78-6

Synonyms Acetic acid ethyl ester

Recommended Use Laboratory chemicals.

Uses advised against

Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

**Emergency Telephone Number** 

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

### Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness



### **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

## Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl acetate	141-78-6	>95

### 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Breathing difficulties. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically

### 5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable Extinguishing Media Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

Flash Point -4 °C / 24.8 °F

Method - Closed cup

Autoignition Temperature 427 °C / 800.6 °F

**Explosion Limits** 

Upper 11.5 vol %
Lower 2.0 vol %
Oxidizing Properties Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2)

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

### 6. Accidental release measures

Personal Precautions Use p

Use personal protective equipment. Ensure adequate ventilation.

**Environmental Precautions** Should not be released into the environment. See Section 12 for additional ecological

information.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** 

	7. Handling and storage
Handling	Ensure adequate ventilation. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.
Storage	Flammables area. Keep away from heat and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

### 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl acetate	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 400 ppm
		(Vacated) TWA: 1400 mg/m <sup>3</sup>	TWA: 400 ppm	TWA: 1400 mg/m <sup>3</sup>
		TWA: 400 ppm	TWA: 1400 mg/m <sup>3</sup>	-
		TWA: 1400 mg/m <sup>3</sup>	_	

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

**Personal Protective Equipment** 

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection** Long sleeved clothing.

**Respiratory Protection**No protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

### Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweetOdor Threshold50 ppm

pH No information available

Melting Point/Range -83.5 °C / -118.3 °F

**Boiling Point/Range** 75 - 78 °C / 167 - 172.4 °F **Flash Point** 75 - 78 °C / 24.8 °F

Method - Closed cup

Evaporation Rate 6.2

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 11.5 vol %

 Lower
 2.0 vol %

Vapor Pressure 103 mbar @ 20°C

Vapor Density3.04Specific Gravity0.902

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition Temperature

Slightly soluble in water
No data available
427 °C / 800.6 °F
No information available

Viscosity 0.45 cP @ 20 °C Molecular Formula C4 H8 O2

Molecular Weight 88.11

Surface tension 24 mN/m @ 20°C

### 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Amines, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Carbon dioxide (CO<sub>2</sub>)

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

### 11. Toxicological information

### **Acute Toxicity**

### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acetate	10,200 mg/kg ( Rat )	> 20 mL/kg ( Rabbit ) > 18000 mg/kg (Rabbit)	58 mg/l (rat; 8 h)

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ponent CAS-No IAR		IARC NTP		OSHA	Mexico	
Ethyl acetate	141-78-6	Not listed					

Mutagenic Effects No information available

Reproductive Effects No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and May cause central nervous system depression: Inhalation of high vapor concentrations may

delayed

inay cause ceritial nervous system depression. Illinatation of right vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

### 12. Ecological information

**Ecotoxicity** 

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl acetate	EC50 = 3300 mg/L/48h	Fathead minnow: LC50: 230	EC50 = 1180 mg/L 5 min	EC50 = 717 mg/L/48h
	_	mg/l/ 96h	EC50 = 1500 mg/L 15 min	_
		Gold orfe: LC50: 270	EC50 = 5870 mg/L 15 min	
		mg/L/48h	EC50 = 7400  mg/L  2  h	

Persistence and Degradability Persiste

Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** 

No information available.

**Mobility** 

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl acetate	0.6

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes		
Ethyl acetate - 141-78-6	U112	-		

## 14. Transport information

DOT

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

**TDG** 

**UN-No** UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group II

**IATA** 

**UN-No** UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3 Packing Group II

IMDG/IMO

**UN-No** UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

### 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	TSCA	DSL	NDSL	<b>EINECS</b>	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl acetate	Χ	Χ		205-500-4	1		Χ	Χ	Χ	Χ	Χ

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl acetate	5000 lb	=

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know

Regulations

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island	
ſ	Ethyl acetate	X	X	Χ	=	X	

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

### **Other International Regulations**

Mexico - Grade Serious risk, Grade 3

	16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 13-Oct-2009

 Revision Date
 23-Jan-2018

 Print Date
 23-Jan-2018

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**