SAFETY DATA SHEET

Version 6.2 Revision Date 05/28/2017 Print Date 10/04/2019

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Lead(II) nitrate

Product Number : 228621 Brand : SIGALD Index-No. : 082-001-00-6

CAS-No. : 10099-74-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 2), H272

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Serious eye damage (Category 1), H318

Carcinogenicity (Category 1B), H350

Reproductive toxicity (Category 1A), H360

Specific target organ toxicity - repeated exposure (Category 2), H373

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H272 May intensify fire; oxidizer.

SIGALD- 228621

H302 + H332 Harmful if swallowed or if inhaled Causes serious eye damage. H318 H350 May cause cancer. May damage fertility or the unborn child. H360 May cause damage to organs through prolonged or repeated exposure. H373 Very toxic to aquatic life with long lasting effects. H410 Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood P210 Keep away from heat. Keep/Store away from clothing/ combustible materials. P220 Take any precaution to avoid mixing with combustibles. P221 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P260 Wash skin thoroughly after handling. P264 Do not eat, drink or smoke when using this product. P270 Use only outdoors or in a well-ventilated area. P271 P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula : N₂O₆Pb

Molecular weight : 331.21 g/mol
CAS-No. : 10099-74-8
EC-No. : 233-245-9
Index-No. : 082-001-00-6

Hazardous components

Component	Classification	Concentration			
Lead nitrate Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)					
	Ox. Sol. 2; Acute Tox. 4; Eye Dam. 1; Carc. 1B; Repr. 1A; STOT RE 2; Aquatic Acute 1; Aquatic Chronic 1; H272, H302 + H332, H318, H350, H360, H373, H410	<= 100 %			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SIGALD- 228621 Page 2 of 10

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NOx), Lead oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Keep away from heat and sources of ignition.

For precautions see section 2.2.

SIGALD- 228621 Page 3 of 10

Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. 7.2

7.3

Specific end use(s)
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

Control parameters
Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis		
			parameters			
Lead nitrate	10099-74-8	TWA	0.050000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Central Nervous System impairment Hematologic effects				
		Peripheral N	pairment			
		Substances for which there is a Biological Exposure Index or Indices				
		(see BEI® section)				
		Confirmed animal carcinogen with unknown relevance to humans varies				
		PEL	0.050000	OSHA Specifically Regulated		
			mg/m3	Chemicals/Carcinogens		
		1910.1025				
		If an employee is exposed to lead for more than 8 hours in any wor				
		day, the permissible exposure limit, as a time weighted average (TWA) for that day, shall be reduced according to the following				
		formula: Maximum permissible limit (in μg/m3)=400÷hours worke				
		in the day				
				upational exposure to lead, except as		
		provided in paragraph (a)(2). It does not apply to the construction industry or to agricultural operations covered by 29 CFR part 1928 OSHA specifically regulated carcinogen				
		TWA	0.050000	USA. NIOSH Recommended		
			mg/m3	Exposure Limits		
		See Append				
		PEL	0.050000	OSHA Specifically Regulated		
			mg/m3	Chemicals/Carcinogens		
		1910.1025				
				ead for more than 8 hours in any work		
				limit, as a time weighted average		
				duced according to the following		
		formula: Max in the day	kimum permissible	e limit (in µg/m3)=400÷hours worked		
		and the second second second				
				upational exposure to lead, except as		
		provided in paragraph (a)(2). It does not apply to the construction industry or to agricultural operations covered by 29 CFR part 1928. OSHA specifically regulated carcinogen				
				arcinogen		
		See 1910.10		LICA ACCILI Throob and Limit Value		
		TWA	0.05 mg/m3	USA. ACGIH Threshold Limit Values (TLV)		
			ous System impa	irment		
Hematologic effe						
			ervous System im			
		Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Confirmed animal carcinogen with unknown relevance to humans varies				
	1	PEL	0.05 mg/m3	OSHA Specifically Regulated		
		•	51.55 III.g. III.			
		1910.1025	area mg/ma	Chemicals/Carcinogens		

SIGALD- 228621 Page 4 of 10

If an employee is exposed to lead for more than 8 hours in any work day, the permissible exposure limit, as a time weighted average (TWA) for that day, shall be reduced according to the following formula: Maximum permissible limit (in µg/m3)=400÷hours worked in the day This section applies to all occupational exposure to lead, except as provided in paragraph (a)(2). It does not apply to the construction industry or to agricultural operations covered by 29 CFR part 1928. OSHA specifically regulated carcinogen				
TWA	0.05 mg/m3	USA. NIOSH Recommended Exposure Limits		
See Appendix C				

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: solid

Colour: white

b) Odour No data available

SIGALD- 228621 Page 5 of 10

c) Odour Threshold No data availabled) pH No data available

e) Melting point/freezing Melting point/range: 470 °C (878 °F) - dec.

point

f) Initial boiling point and No data available boiling range

g) Flash point ()No data available
h) Evaporation rate No data available
i) Flammability (solid, gas) No data available

j) Upper/lower No data available flammability or

k) Vapour pressure No data availablel) Vapour density No data availablem) Relative density 4.53 g/cm3

n) Water solubility 500 g/l

 o) Partition coefficient: noctanol/water

explosive limits

No data available

p) Auto-ignition No data available temperature

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties The substance or mixture is classified as oxidizing with the category 2.

9.2 Other safety information

Solubility in other Ethanol 0.4 g/l solvents Methanol 13.3 g/l

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong reducing agents, Organic materials, Powdered metals

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Nitrogen oxides (NOx), Lead oxides Other decomposition products - No data available

In the event of fire: see section 5

SIGALD- 228621 Page 6 of 10

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data availableLead nitrate

Inhalation: No data available(Lead nitrate)
Dermal: No data available(Lead nitrate)

LD50 Intravenous - Rat - 93 mg/kg(Lead nitrate) LD50 Intraperitoneal - Mouse - 74 mg/kg(Lead nitrate)

Skin corrosion/irritation

No data available(Lead nitrate)

Serious eye damage/eye irritation

No data available(Lead nitrate)

Respiratory or skin sensitisation

No data available(Lead nitrate)

Germ cell mutagenicity

No data available(Lead nitrate)

Carcinogenicity

IARC: 2A - Group 2A: Probably carcinogenic to humans (Lead nitrate)

2A - Group 2A: Probably carcinogenic to humans (Lead nitrate)

NTP: RAHC - Reasonably anticipated to be a human carcinogenThe reference note has been

added by TD based on the background information of the NTP. (Lead nitrate)

OSHA: OSHA specifically regulated carcinogen (Lead nitrate)

Reproductive toxicity

Known human reproductive toxicant(Lead nitrate)

No data available(Lead nitrate)

No data available(Lead nitrate)

Specific target organ toxicity - single exposure

No data available(Lead nitrate)

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

No data available(Lead nitrate)

Additional Information

RTECS: OG2100000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., Lead salts have been reported to cross the placenta and to induce embryo- and feto- mortality.(Lead nitrate)

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence(Lead nitrate)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 1.5 mg/l - 96.0 h(Lead nitrate)

LC50 - Cyprinus carpio (Carp) - 0.4 - 1.3 mg/l - 96.0 h(Lead nitrate)

SIGALD- 228621 Page 7 of 10

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 0.5 - 2.0 mg/l - 48 h(Lead nitrate) other aquatic invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available(Lead nitrate)

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chem scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1469 Class: 5.1 (6.1) Packing group: II

Proper shipping name: Lead nitrate

Reportable Quantity (RQ) : 10 lbs

Marine pollutant: no

Poison Inhalation Hazard: No

IMDG

UN number: 1469 Class: 5.1 (6.1) Packing group: II EMS-No: F-A, S-Q

Proper shipping name: LEAD NITRATE Marine pollutant : yesMarine pollutant : yes

IATA

UN number: 1469 Class: 5.1 (6.1) Packing group: II

Proper shipping name: Lead nitrate

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date

SIGALD- 228621 Page 8 of 10

Lead nitrate 10099-74-8 1993-04-24

SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Lead nitrate CAS-No. Revision Date 10099-74-8 1993-04-24

Pennsylvania Right To Know Components

CAS-No. Revision Date Lead nitrate 10099-74-8 1993-04-24

New Jersey Right To Know Components

CAS-No. Revision Date Lead nitrate 10099-74-8 1993-04-24

California Prop. 65 Components

WARNING! This product contains a chemical known to the CAS-No. Revision Date State of California to cause cancer 10099-74-8 2007-09-28

Lead nitrate

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H272 May intensify fire; oxidizer. H302 Harmful if swallowed.

H302 + H332 Harmful if swallowed or if inhaled H318 Causes serious eve damage.

H332 Harmful if inhaled. H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 0
Physical Hazard 2

NFPA Rating

Health hazard: 2
Fire Hazard: 0
Reactivity Hazard: 2
Special hazard.I: OX

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

SIGALD- 228621 Page 9 of 10

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 6.2 Revision Date: 05/28/2017 Print Date: 10/04/2019

SIGALD- 228621 Page 10 of 10