

SAFETY DATA SHEET

Creation Date 26-Oct-2009

Revision Date 23-Jan-2018

Revision Number 3

1. Identification

AC445720000; AC445720010; AC445720025

Product	Name	n-Hexane

Cat No. :

Synonyms

CAS-No

F

110-54-3 Hex

Recommended Use Uses advised against Laboratory chemicals. Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Acros Organics One Reagent Lane Fair Lawn, NJ 07410

Emergency Telephone Number

For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11 Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No.US:001-800-424-9300 / Europe:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2	
Skin Corrosion/irritation	Category 2	
Serious Eye Damage/Eye Irritation	Category 2	
Reproductive Toxicity	Category 2	
Specific target organ toxicity (single exposure)	Category 3	
Target Organs - Respiratory system, Central nervous syste	em (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 1	
Target Organs - Liver, Heart, Blood.		
Aspiration Toxicity	Category 1	

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation

May cause drowsiness or dizziness Suspected of damaging fertility Causes damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Hexane	110-54-3	>95

4. First-aid measures			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.		
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Obtain medical attention. Aspiration into lungs can produce severe lung damage.		
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs, lean victim forward to reduce the risk of aspiration.		
Most important symptoms and effectsBreathing difficulties. Inhalation of high vapor concentrations may cause symptoms headache, dizziness, tiredness, nausea and vomiting Treat symptomaticallyNotes to PhysicianTreat symptomatically			
	5. Fire-fighting measures		
Suitable Extinguishing Media	CO 2, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray.		
Unsuitable Extinguishing Media Water may be ineffective, This material is lighter than water and insoluble in could easily be spread by the use of water in an area where the water cannot			
Flash Point	-22 °C / -7.6 °F		
Method - No information available			
Autoignition Temperature	223 °C / 433.4 °F		
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	7.5 vol % 1.1 vol % t No information available No information available		

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA Health 2	Flammability 3	Instability 0	Physical hazards N/A		
	6. Accidental release measures				
Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.				
Environmental Precautions	Do not flush into surface water or sanitary sewer system. Avoid release to the environmer Collect spillage.		Avoid release to the environment.		

Methods for Containment and CleanSoak up with inert absorbent material. Keep in suitable, closed containers for disposal.UpRemove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take
precautionary measures against static discharges.

	7. Handling and storage
Handling	Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm	TWA: 50 ppm TWA: 176 mg/m ³
	OKIT	TWA: 500 ppm	TWA: 180 mg/m ³	TWA. Tro mg/m
		TWA: 1800 mg/m ³	-	

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

 Engineering Measures
 Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

 Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

	9. Physical and chemical properties
Physical State Appearance	Liquid Colorless
Odor	Petroleum distillates
Odor Threshold	No information available
pH Melting Point/Range	Not applicable -95 °C / -139 °F
Boiling Point/Range	69 °C / 156.2 °F @ 760 mmHg
Flash Point	-22 °C / -7.6 °F
Evaporation Rate	No information available

Not applicable 7.5 vol % 1.1 vol % 160 mbar @ 20 °C

2.97 0.659 immiscible No data available 223 °C / 433.4 °F No information available 0.31 mPa s at 20 °C C6 H14 86.18

10. Stability and reactivity			
Reactive Hazard None known, based on information available			
Stability	Stable under normal conditions.		
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Exposure to light. Keep away from open flames, hot surfaces and sources of ignition.		
Incompatible Materials	Strong oxidizing agents, Halogens		
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)			
Hazardous Polymerization Hazardous polymerization does not occur.			
Hazardous Reactions None under normal processing.			

11. Toxicological information

Acute Toxicity

Product Information

Component information			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat)4 h
Toxicologically Synergistic	No information available		

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico	
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed	
Mutagenic Effects		Mutagenic effects	have occurred in e	xperimental anima	ıls.		
Reproductive Effect	S	Experiments have shown reproductive toxicity effects on laboratory animals.					
Developmental Effe	cts	Developmental effects have occurred in experimental animals.					
Teratogenicity		Teratogenic effects have occurred in experimental animals.					

STOT - single exposure STOT - repeated exposure	Respiratory system Central nervous system (CNS) Liver Heart Blood
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	Tumorigenic effects have been reported in experimental animals. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h
Persistence and Degradability Persistence		is unlikely based on inform	ation available.	
Bioaccumulation/ Accumulation No information		on available.		
Mobility Will likely be mobile in t		mobile in the environment	due to its volatility.	
	Component		log Pow	
	Hexane		4 11	

Component	log Pow
Hexane	4.11

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1208
Proper Shipping Name	HEXANES
Hazard Class	3
Packing Group	II
<u>IATA</u>	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3
Packing Group	II

15. Regulatory information

All of the components in the product are on the following Inventory lists: Australia Complete Regulatory Information contained in following SDS's X = listed China Canada The product is classified and labeled according to EC directives or corresponding national laws The product is classified and labeled in accordance with Directive 1999/45/EC Europe TSCA Korea Philippines Japan U.S.A. (TSCA) Canada (DSL/NDSL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (ECL) China (IECSC) Japan (ENCS) Philippines (PICCS)

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Hexane	Х	Х	-	203-777-6	438-390		Х	Х	Х	Х	Х
					-3						

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Hexane	110-54-3	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	X		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

Dogulations

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component		Hazardous Substances RQs	CERCLA EHS RQs
Hexane		5000 lb	-
California Proposition 65	This product does not contain any Proposition 65 chemicals		

California Proposition 65

U.S. State Right-to-Know

Negulations					
Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hexane	X	Х	Х	Х	X

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade	de Serious risk, Grade 3					
	16. Other information					
Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com					
Creation Date Revision Date Print Date Revision Summary	26-Oct-2009 23-Jan-2018 23-Jan-2018 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).					

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS